

Package: rle (via r-universe)

September 11, 2024

Version 0.9.2-234

Date 2020-12-24

Title Common Functions for Run-Length Encoded Vectors

Description Common 'base' and 'stats' methods for 'rle' objects, aiming to make it possible to treat them transparently as vectors.

Depends R (>= 3.5)

Imports methods

Copyright file inst/COPYRIGHT

BugReports <https://github.com/statnet/rle/issues>

License GPL-3

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Encoding UTF-8

Suggests covr

Repository <https://statnet.r-universe.dev>

RemoteUrl <https://github.com/statnet/rle>

RemoteRef HEAD

RemoteSha d08b185ab504aaa13e2fa44f8ec9b1bcaeb76db0

Contents

rle-package	2
as.rle	2
compress	3
compress.rle	3
Extract.rle	4
Math.rle	5
Ops.rle	6
rep.rle	7

rle-deprecated	8
rle-methods	9
Summary.rle	10

Index	12
--------------	-----------

rle-package	<i>The rle Package</i>
-------------	------------------------

Description

Common `base` and `stats` methods for `rle` objects, aiming to make it possible to treat them transparently as vectors.

History

This package grew out of the needs of the `ergm` package for a run-length encoded representation of extremely long vectors with a small number of contiguous runs, and these functions were originally implemented in the `statnet.common` package.

It has been split out into its own package to enable others to use this functionality without installing any unnecessary dependencies and to facilitate contributions under a simplified license.

What works and what doesn't

The long-run aim of this package is to make it possible to treat `rle` objects transparently as unnamed vectors. As of this writing, the biggest unimplemented feature are:

- The indexing (`[]` and `[[]`) operators. It is not possible to extract or replace individual elements of the vector represented by an `rle` object, though it is possible to access its underlying representation (i.e., `$lengths` and `$values`) by name using any of the above operators or the `$` operator.
- Method `rep.rle` currently has limited functionality.

as.rle	<i>Coerce to <code>rle</code> if not already an <code>rle</code> object</i>
--------	-----------------------------------------------------------------------------

Description

Coerce to `rle` if not already an `rle` object

Usage

```
as.rle(x)

## S3 method for class 'rle'
as.rle(x)

## Default S3 method:
as.rle(x)
```

Arguments

x the object to be coerced.

compress *A generic function for compressing a data structure.*

Description

A generic function for compressing a data structure.

Usage

```
compress(x, ...)
```

Arguments

x the object to be compressed.
 ... additional arguments to methods.

compress.rle *Compress the [rle](#) object by merging adjacent runs*

Description

Compress the [rle](#) object by merging adjacent runs

Usage

```
## S3 method for class 'rle'
compress(x, ...)
```

Arguments

x an [rle](#) object.
 ... additional objects; if given, all arguments are concatenated.

Note

Since [rle](#) stores run lengths as integers, [compress.rle](#) will not merge runs that add up to lengths greater than what can be represented by a 32-bit signed integer (2147483647).

Examples

```
x <- rle(as.logical(rbinom(10,1,.7)))
y <- rle(as.logical(rbinom(10,1,.3)))

stopifnot(identical(rle(inverse.rle(x)&inverse.rle(y)),compress(x&y)))

big <- structure(list(lengths=as.integer(rep(.Machine$integer.max/4,6)),
                    values=rep(TRUE,6)), class="rle")

stopifnot(all(aggregate(as.numeric(lengths)~values,
                       data=as.data.frame(unclass(big)),FUN=sum)
             ==
             aggregate(as.numeric(lengths)~values,
                       data=as.data.frame(unclass(compress(big))),
                       FUN=sum)))
```

 Extract.rle

Indexing Methods for rle Objects

Description

These methods are defined and produce an error (except for [character](#) input) to future-proof code that depends on the rle package by preventing their use.

Usage

```
## S3 method for class 'rle'
x[i, ...]

## S3 replacement method for class 'rle'
x[i, ...] <- value

## S3 method for class 'rle'
x[[i, ...]]

## S3 replacement method for class 'rle'
x[[i, ...]] <- value

## S3 method for class 'rle'
x$name

## S3 replacement method for class 'rle'
x$name <- value
```

Arguments

x, i, name, value, ...

Arguments to indexing operators. See [Extract](#) documentation in the base package.

Details

At this time, the `rle` package does not support indexing operations by `logical` or `numeric` indices, but it is likely to do so in the future. Therefore, we reserve the syntax now to prevent users of this package from relying on the default behaviour of the indexing operators.

Value

At this time, all functions raise an error except for `character` indices. This behaviour can be overridden by setting `options(rle.unclass_index=TRUE)`, which effectively `unclasses` the objects before indexing.

Examples

```
# Indexing by character or by $ works, including sub-indexing.
x <- rle(1:5)
x[["values"]] <- 2:6
x
x$values[2:3] <- 7:8
x

## Not run:
# Numerical indexing doesn't, unless `options(rle.unclass_index=TRUE)` is set.
x[1]
x[[1]]

## End(Not run)
```

 Math.rle

Mathematical functions for `rle` Objects

Description

Mathematical functions that work independently elementwise on vectors described in `Math` are implemented for `rle` objects. See Details for list of exceptions.

Usage

```
## S3 method for class 'rle'
Math(x, ...)
```

Arguments

```
x          An rle object.
...       Additional arguments.
```

Details

Supported functions include all elements of the S3 [Math](#) group excluding the "cumulative" ones, which are not supported at this time and will raise an error. As of this writing, functions supported include (from R help) `abs`, `sign`, `sqrt`, `floor`, `ceiling`, `trunc`, `round`, `signif`, `exp`, `log`, `expm1`, `log1p`, `cos`, `sin`, `tan`, `cospi`, `sinpi`, `tanpi`, `acos`, `asin`, `atan`, `cosh`, `sinh`, `tanh`, `acosh`, `asinh`, `atanh`, `lgamma`, `gamma`, `digamma`, and `trigamma`.

Functions `cumsum`, `cumprod`, `cummax`, and `cummin` are not supported at this time and will raise an error.

Value

In every supported case, the call should result in an [rle](#) that would have resulted had the call been applied to the original (uncompressed) vector, then compressed using [rle](#). (At no point in the calculation is the uncompressed vector actually constructed, of course.)

By default, the functions do not merge adjacent runs with the same value. This must be done explicitly with [compress.rle](#).

Examples

```
x <- rle(sample(runif(2), 10, c(.7,.3), replace=TRUE))

stopifnot(isTRUE(all.equal(sin(inverse.rle(x)), inverse.rle(sin(x)))))
stopifnot(inherits(try(cumprod(x)), "try-error"))
```

Ops.rle

Unary and Binary Operations for [rle](#) Objects

Description

Unary and binary [Arithmetic](#) and [Logic](#) operators (with exceptions given below) are implemented between two [rle](#) objects and between an [rle](#) object and a scalar.

Usage

```
## S3 method for class 'rle'
Ops(e1, e2)
```

Arguments

`e1, e2` Arguments to unary (`e1`) and binary (`e1` and `e2`) operators.

Details

Supported operations include all elements of the [Ops](#) group, as well as [xor](#). Within the [Arithmetic](#) and [Logic](#) operators, this includes (taken from the R help): `+`, `-`, `*`, `/`, `^`, `<`, `>`, `<=`, `>=`, `!=`, `==`, `%/`, `%%`, `&`, `|`, `!`, and `xor`; but excludes non-vector logical functions and operators such as [isTRUE](#) and [&&](#).

Value

In every supported case, the operation should result in an `rle` that would have resulted had the operation been applied to the original (uncompressed) vectors, then compressed using `rle`, with the proviso that if the resulting function creates adjacent runs of the same value, they are *not* merged. This must be done explicitly with `compress.rle`. (At no point in the calculation are the uncompressed vectors actually constructed, of course.)

An operation between an `rle` and a zero-length object produces an empty `rle`.

Examples

```
x <- rle(as.logical(rbinom(10,1,.7)))
y <- rle(as.logical(rbinom(10,1,.3)))

stopifnot(isTRUE(all.equal(!inverse.rle(x),inverse.rle(!x))))

stopifnot(isTRUE(all.equal((inverse.rle(x)|inverse.rle(y)),inverse.rle(x|y))))

stopifnot(isTRUE(all.equal((inverse.rle(x)&inverse.rle(y)),inverse.rle(x&y))))

x <- rle(sample(c(-1,+1), 10, c(.7,.3), replace=TRUE))
y <- rle(sample(c(-1,+1), 10, c(.3,.7), replace=TRUE))

stopifnot(isTRUE(all.equal((inverse.rle(x)*inverse.rle(y)),inverse.rle(x*y))))
stopifnot(isTRUE(all.equal((2*inverse.rle(y)),inverse.rle(2*y))))
stopifnot(isTRUE(all.equal((inverse.rle(x)*2),inverse.rle(x*2))))

stopifnot(isTRUE(all.equal((inverse.rle(x)/inverse.rle(y)),inverse.rle(x/y))))
stopifnot(isTRUE(all.equal((2/inverse.rle(y)),inverse.rle(2/y))))
stopifnot(isTRUE(all.equal((inverse.rle(x)/2),inverse.rle(x/2))))

stopifnot(isTRUE(all.equal((-inverse.rle(y)),inverse.rle(-y))))
stopifnot(isTRUE(all.equal((inverse.rle(x)-inverse.rle(y)),inverse.rle(x-y))))

stopifnot(isTRUE(all.equal((inverse.rle(x)%inverse.rle(y)),inverse.rle(x%/y))))

stopifnot(isTRUE(all.equal(inverse.rle(x)==inverse.rle(y),inverse.rle(x==y))))

stopifnot(isTRUE(all.equal((inverse.rle(x)>inverse.rle(y)),inverse.rle(x>y))))
```

rep.rle

A `rep` method for `rle` objects

Description
A `rep` method for `rle` objects

Usage

```
## S3 method for class 'rle'
rep(
  x,
  ...,
  scale = c("element", "run"),
  doNotCompact = FALSE,
  doNotCompress = doNotCompact
)
```

Arguments

`x` an `rle` object.

`...` see documentation for `rep`.

`scale` whether to replicate the elements of the RLE-compressed vector or the runs.

`doNotCompress, doNotCompact` whether the method should call `compress.rle` the results before returning. Methods liable to produce very long output vectors, like `rep`, have this set FALSE by default. `doNotCompact` is an old name for this argument.

Note

The `rep` method for `rle` objects is very limited at this time. Even though the default setting is to replicate elements of the vector, only the run-replicating functionality is implemented at this time except for the simplest case (scalar times argument).

Examples

```
x <- rle(sample(c(-1,+1), 10, c(.7,.3), replace=TRUE))
y <- rpois(length(x$lengths), 2)

stopifnot(isTRUE(all.equal(rep(inverse.rle(x), rep(y, x$lengths)),
                             inverse.rle(rep(x, y, scale="run")))))

stopifnot(isTRUE(all.equal(rep(inverse.rle(x), max(y)),
                             inverse.rle(rep(x, max(y), scale="element")))))
```

rle-deprecated

Deprecated functions from rle

Description

Deprecated functions from `rle`

Usage

```
compact.rle(...)
```


Arguments

... arguments to deprecated functions.

rle-methods

Miscellaneous Common Methods for rle Objects

Description

Miscellaneous Common Methods for `rle` Objects

Usage

```
## S3 method for class 'rle'
c(...)

## S3 method for class 'rle'
mean(x, na.rm = FALSE, ...)

## S3 method for class 'rle'
length(x)

## S3 method for class 'rle'
is.na(x)

## S3 method for class 'rle'
str(object, ...)
```

Arguments

... For `c`, objects to be concatenated. The first object must be of class `rle`.

`x, object` An `rle` object.

`na.rm` Whether missing values are to be ignored (TRUE) or propagated (FALSE).

Note

The `length` method returns the length of the vector represented by the object, obtained by summing the lengths of individual runs. This can be overridden by setting `options(rle.unclass_index = FALSE)`, which causes it to return the length of the underlying representation (usually 2) instead.

Examples

```
x <- rle(as.logical(rbinom(10,1,.7)))
y <- rle(as.logical(rbinom(10,1,.3)))

stopifnot(isTRUE(all.equal(c(inverse.rle(x),inverse.rle(y)),inverse.rle(c(x,y)))))
```

```

stopifnot(isTRUE(all.equal(mean(inverse.rle(x)),mean(x))))
stopifnot(isTRUE(all.equal(mean(inverse.rle(y)),mean(y))))

stopifnot(isTRUE(all.equal(length(inverse.rle(x)),length(x))))
stopifnot(isTRUE(all.equal(length(inverse.rle(y)),length(y))))

x$values[1] <- NA
y$values[1] <- NA
stopifnot(isTRUE(all.equal(is.na(inverse.rle(x)),inverse.rle(is.na(x)))))
stopifnot(isTRUE(all.equal(is.na(inverse.rle(y)),inverse.rle(is.na(y)))))

str(x)

```

Summary.rle

Summary methods for rle objects.

Description

Summarisation functions for vectors described in [Summary](#) are implemented for [rle](#) objects.

Usage

```

## S3 method for class 'rle'
Summary(..., na.rm)

```

Arguments

... [rle](#) objects or objects that can be coerced to [rle](#).

na.rm Whether the missing values should be ignored (TRUE) or propagated (FALSE).

Details

Supported functions include all elements of the S3 [Summary](#) group. As of this writing, functions supported include (from R help) all, any, max, min, prod, range, and sum.

Value

In every supported case, the call should produce the same result as what would have resulted had the call been applied to the original (uncompressed) vector. (At no point in the calculation is the uncompressed vector actually constructed, of course.) The exception is that if values are of class `integer`, the result will nonetheless always be upcast to `numeric` to avert overflows. This behaviour may change in the future.

Examples

```
x <- rle(as.logical(rbinom(20,1,.7)))
y <- rle(as.logical(rbinom(20,1,.3)))

stopifnot(isTRUE(all.equal(any(x, y),any(inverse.rle(x), inverse.rle(y)))))
stopifnot(isTRUE(all.equal(any(y),any(inverse.rle(y)))))

stopifnot(isTRUE(all.equal(sum(inverse.rle(x),inverse.rle(y)),sum(x,y))))
stopifnot(isTRUE(all.equal(sum(inverse.rle(y)),sum(y))))

y$values[2:3] <- NA
stopifnot(isTRUE(all.equal(sum(inverse.rle(y), na.rm=TRUE),sum(y, na.rm=TRUE))))
stopifnot(isTRUE(all.equal(sum(inverse.rle(y), na.rm=FALSE),sum(y, na.rm=FALSE))))
```

Index

[.rle (Extract.rle), 4
[<-.rle (Extract.rle), 4
[[.rle (Extract.rle), 4
[[<-.rle (Extract.rle), 4
\$.rle (Extract.rle), 4
\$<-.rle (Extract.rle), 4
&&, 6

Arithmetic, 6
as.rle, 2

base, 2

c.rle (rle-methods), 9
character, 4, 5
compact.rle (rle-deprecated), 8
compress, 3
compress.rle, 3, 3, 6–8

Extract, 4
Extract.rle, 4

is.na.rle (rle-methods), 9
isTRUE, 6

length, 9
length.rle (rle-methods), 9
Logic, 6
logical, 5

Math, 5, 6
Math.rle, 5
mean.rle (rle-methods), 9

numeric, 5

Ops.rle, 6

rep, 7, 8
rep.rle, 2, 7
rle, 2, 3, 5–10

rle-deprecated, 8
rle-methods, 9
rle-package, 2

stats, 2
str.rle (rle-methods), 9
Summary, 10
Summary.rle, 10

unclass, 5

xor, 6